



MiRAGE PRO CVTF

- MiRAGE PRO CVTF is suitable for the lubrication of Continuous Variable Transmission (CVT) for the following OEM requirements :
 - Audi/VW (TL 52180; G 052 180)
 - Daihatsu AMMiX CVT Fluid-DC, CVT Fluid-DFE
 - GM/Saturn Dex-CVT
 - Honda HCF-2
 - Hyundai/Kia SP-CVT1
 - Mini Cooper EZL 799A
 - Mitsubishi DiaQueen CVTF J4
 - Nissan CVT Fluid NS-2/NS-3
 - Subaru Lineartronic CVTF
 - Suzuki (CVTF 3320, TC, NS-2, CVTF Green 1, CVTF Green 2)
 - Toyota CVT Fluid FE
- The key performance of this fluid includes low temperature fluidity, high thermo-oxidative stability, wear and foaming resistance, excellent friction properties together with anti-shudder durability and smooth drivability.
- Never over-refuel and mix with engine oils.
- The fluid is red to distinguish it.
- Packages : 1 liter bottle, 1 liter*12 case
- The typical properties are listed as follows :

Specific Gravity, 15.6/15.6°C, D4052	0.8540
Viscosity, Kin., cSt @40°C, D445	36.2
@100°C, D445	7.20
Viscosity Index, D2270	168
Flash Point, COC, °C, D92	205
Pour Point, °C, D6749	-42
Color, Visual	Red
Product No.	LM55116

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.