



CPC Rock Drill Oil 100

- CPC Rock Drill Oil 100 is highly refined and added special oil component. The oil possesses strong metal surface adhesion that can form tenacious oil film to resist humidity corrosion and lubricate the machines with vibration load such as rock-drill equipment, air compressors and electric tools etc.
- The oil is a very excellent metal process oil for lubrication in cutting non-ferrous metal, such as aluminum, magnesium, and copper, and manufacturing Cu-Wire, Al-Wire, Steel-Wire, and etc. The oil can be diluted by kerosene, diesel fuel and spindle oil.
- Package: 200 liter drum.
- The typical data are listed as follow:

Viscosity Grade, ISO VG	100
Sp. Gr., 15.6°C/15.6°C, D4052	0.9038
Viscosity, Kin., cSt @40°C, D445	100.0
@100°C, D445	11.23
Viscosity Index, D2270	98
Pour Point, °C, D6749	-12
Flash Point, COC, °C, D92	238
Color, D1500	L1.5
Acid Number, mg KOH/g, D664	0.04
Carbon Residue, Rams., %, D524	0.31
Product No.	LA75100

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.