



CPC 9000 SM Motor Oil 10W/40, 5W/50

- CPC 9000 SM Motor Oils are API SM certified and are applied to gasoline engine vehicles which require SM grade oil.
- Manufactured with fully synthetic base oils and top formula technologies. The oil film is very stable and possesses excellent oxidation resistance and pour effect in low temperature. The oils are the best for all seasons and suitable for highway and city driving mode. The draining mileage is much longer than conventional mineral oils.
- The oils are blended in new phosphorus environmental-friendly formulations which can offer motor engine more wear reduction, engine cleaning and engine life prolongation with catalyst converter. They can fully replace the SL, SJ, SH, or SG earlier grade oils and provide better lubrication for the modern vehicles.
- Package: 1 liter bottle, 1 liter*12 case
- The typical data are listed as follow:

SAE Viscosity No.	10W/40	5W/50
Sp. Gr., 15.6°C/15.6°C, D4052	0.8585	0.8552
Viscosity Kin., cSt@40°C, D445	93.4	105.5
@100°C, D445	14.21	17.65
Viscosity Index, D2270	157	183
HTHS, cP (10^6 s^{-1}), D5481	4.17	4.16
Flash Point, COC, °C, D92	224	220
Fire Point, COC, °C, D92	250	242
Acid Number, mg KOH/g, D664	1.72	1.75
Base Number, mg KOH/g, D2896	6.34	7.22
API Service Classification	SM	SM
Product No.	LB51510	LB51520

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.