



CPC 9000 SP Motor Oil 5W/30

- CPC 9000 SP Motor Oil 5W/30 is approval by the API Engine Oil Licensing & Certification System(EOLCS).
- The viscosity grade of this product is 5W/30 and it adopts the synthetic base oil with high performance and modern formulation technology. This oil balances the excellent anti-oxidation and anti-wear ability and is highly suitable for Asian high way and city driving mode with long oil drain interval.
- This oil balances robust oil film and contributes to fuel efficiency. It can effectively reduces the occurrences of Low Speed Pre-ignition(LSPI) and wear of timing chain, ensuring stable power output of small direct-injection engines equipped with turbocharger.
- This oil is extremely suitable for gasoline fuelled vehicles equipped with the catalytic converter. It offers wear reduction 、engine cleaning 、gasoline saving and prolongation of engine lifetime. If the 5W/30 viscosity grade is recommended by the OEM, this product supersedes API SL, SM, SN and the previous engine oil products.
- Package: 1 liter bottle, 1 liter*12 case
- The typical test results are as follows:

SAE Viscosity No.	5W/30
Viscosity Kin., cSt@40 °C, D445	57.6
@100 °C, D445	10.0
Viscosity Index, D2270	162
HTHS, cP (10 ⁶ s ⁻¹), D5481	3.1
Flash Point, COC, °C, D92	220
Fire Point, COC, °C, D92	244
Pour Point, °C, D6749	-36
TBN, mg KOH/g, D2896	6.3
Sulfated Ash, wt%, D874	0.73
API Service Classification	SP
Product No.	LB51682



Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.