



CPC 9000 SN Motor Oil 10W/40

- CPC 9000 SN Motor Oil is API SN certified and is applied to gasoline engine vehicles which require the latest SN grade oil.
- The Viscosity of the oil is SAE 10W/40. The oil is manufactured with fully synthetic base oils and the latest formula technologies. The oil film is very stable and possesses excellent oxidation resistance and low temperature fluid stability. The oil is the best for all seasons and suitable for highway and city driving mode. The draining mileage is much longer than conventional mineral oils.
- The oil is blended in the latest environmental-friendly formulations which can offer motor engine more wear reduction, engine cleaning and engine life prolongation with catalyst converter and exhaust emission control system. It can fully replace the SM, SL, or SJ earlier grade oils and provide better lubrication for the modern vehicles.
- Package: 1 liter bottle, 1 liter*12 case
- The typical data are listed as follow:

SAE Viscosity No.	10W/40
Sp. Gr., 15.6°C/15.6°C, D4052	0.8541
Viscosity Kin., cSt@40°C, D445	96.19
@ 100°C, D445	14.68
Viscosity Index, D2270	159
HTHS, cP (10^6 s^{-1}), D5481	3.9
Flash Point, COC, °C, D92	224
Fire Point, COC, °C, D92	250
Acid Number, mg KOH/g, D664	1.8
Base Number, mg KOH/g, D2896	7.0
API Service Classification	SN
Product No.	LB51610

Note: Typical properties are based on standard tests under laboratory conditions. Variations that do not affect product performance are to be expected during normal manufacture. Please consult your local CPC representative if you have any questions.