Safety Data Sheet

No：L378　　CPC 9000SN Motor Oil 10W/400　　Ver. 4.0

I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL Product Name: CPC 9000SN Motor Oil 10W/40

OTHER NAME: — —

Product Code:LB51610

Manufacturer Name: Lubricants Business Division, CPC Corporation, Taiwan
Address: 3F, No. 3, Jianguo 1st Rd., Lingya Dist., Kaohsiung City 802, Taiwan, R.O.C.
Telephone Number: 886-7-5361510

Emergency Telephone Number:
886-5-2224171 Ext. 7252
886-5-2224171 Ext. 7230
Fax Number: 886-5-2232062

II. HAZARDS IDENTIFICATION

NFPA Ratings (Scale 0-4): NFPA Fire=1

The Most Important Hazardous Effects:
1. Adverse Human Health Effects:
(For Long Term Exposure)

- Eye Contact:irritation.
- Skin Contact :may cause dermatitis.
- Inhalation: inhalation of oil mist or vapors at elevated temperature may cause respiratory irritation.
- Ingestion:no information is available .

2. Environmental Effects: no information is available.
3. Physical and Chemical Hazards: Mist or vapors can produce at elevated temperatures.
4. Specific Hazards: no information on significant adverse effects.

Main Symptoms:

- Eye Contact : irritation.
- Skin Contact : no information is available.
- Inhalation : no information on significant adverse effects.
- Ingestion : no information is available.

III. COMPOSITION, INFORMATION ON INGREDIENT

1. Product Identification:

Chemical Family: Petroleum Hydrocarbons
Chemical Formula: Mixture
Trade Name/Synonym: Not assigned

2. Component:

Ingredients	CAS Number	% by wt.
Synthetic Base Oil	64742-70-7	80.0~85.0%
Viscosity Improver	9010-79-1	10.0~12.0%
ZINC ALKYL DITHIOPHOSPHATE	68649-42-3	8.0~9.0%

IV. FIRST AID MEASURE

Emergency Procedures:

- Inhalation :
  Remove personnel from exposure area to fresh air immediately. If breathing is difficult, giveoxygen. Ifbreathingceases, use a oxygen rescuer or similar device to perform artificialrespiration. Get medicalattention immediately.
- Skin Contact :
  Remove contaminated clothing, jewelry and shoes immediately. Wash with soap or mild detergent andlargeamounts of water until noevidence ofchemicalremains (atleast 15～20 minutes).Ifirritation oradversesymptomsdevelop, seek medical attention.
- Eye Contact :
  Flush eyes immediately with running water for at least fifteenminutes,occasionally lifting upper and lower lids, until noevidence of chemicalremains. Get medicalattention immediately.
- Digestion :
  If vomiting occurs, keep head lower than hips to help prevent aspiration. Get medical attention.

Protection of First-aider: no information is available.

Notes to Physician: no information is available.

V. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: regular dry chemical, carbon dioxide, water, regular Foam.
Large fires: Use regular foam or flood with fine water spray.

Specific Hazards: Incomplete burning can produce carbon monoxide and/or carbon dioxide and other harmful products.

Special Fire Fighting Procedures:

1. Firefighters should wear proper protective equipment stay upwind.
2. Move container from fire area and shut off source if it can be done without risk.
3. Cool containers with water spray until well after the fire is out.
4. Do not scatter spilled material with high-pressure water streams.
5. Keep unnecessary people away,isolate hazard area and deny entry.
6. Avoid inhalation of material or combustion by-products.

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions:
1. Avoid heat, flames, sparks and other sources of ignition.
2. Stop leak if possible without personal risk.
3. Reduce vapors with water spray.

Environmental Precautions:
1. Eliminate all open flame in vicinity of spill or released vapor.
2. Stop the source of the leak or release.
3. Clean up releases as soon as possible.
4. Contain liquid to prevent further contamination ofsoil, surface wateror groundwater.

Methods for Cleaning Up:
1. Clean up small spills using sand or other non-combustible material.
2. Collect spilled material in appropriate container for disposal.
3. Wherefeasible and appropriate, remove contaminated soil.
4. Follow prescribed proceduresfor reportingand responding to largerreleases.

VII. HANDLING AND STORAGE

Handling:
1. Wear protective equipment, if exposure conditions warrant.
2. Wash thoroughly after handling.
3. Use with adequate ventilation.
4. Handle in accordance with all current regulations and standards.

Storage:
1. Keep away from heat, sparks and flames.
2. Store in well-ventilated area.
3. Store in a tightly closed container.
4. Store in a cool, dry place.
5. Bond and ground during transfer.
6. Keep separated from incompatible substances.
7. Storage in accordance with all current regulations and standards.

VIII. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Engineering Control:

Provide local exhaust ventilation system. Ensure compliance withapplicable exposure limits.

Control Parameter:

HAZARDOUS MATERIAL	TWA	STEL	CEILING
Mineral Oil Mist	ACGIH: 5 mg/m^3 NIOSH: 5 mg/m^3 OSHA : 5 mg/m^3	NIOSH : 10mg/m^3 UK OES : 10mg/m^3	--

Personal Protection Equipment:

- Respiratory Protection:
  Not generally required unless needed to preventrespiratoryirritation. In case of spill or leak resulting inunknownconcentration, use NOISH approved suppliedairrespirator.
- Hand Protection:
  Wear appropriate chemical resistant gloves.
- Eye Protection:
  Wear splash resistant safety gogglesorface shield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.
- Skin and Body Protection:
  Wear appropriate chemical resistant clothing. Remove any chemical soakedclothing immediately.

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: liquid	Form: brown viscous liquid
Color: brown	Odor no specific irritant odor
PH: Not available	Boiling Point/Range: **Not available**
Decomposition Temperature: No data	Flash Point: 224℃ Test Method: Open Cup
Autoignition Temperature: No data	Flammable Limits: Notavailable
Vapor Pressure: <0.1 Kpa@20℃	Vapor Density: >5
Specific Gravity:0.8541g/cm^3 @ 15.6℃	Solubility: insoluble in water

X. STABILITY AND REACTIVITY

Stability: Stable at normal temperatures and pressure.

Possible Hazardous Reactions: Will not polymerize.

Conditions to Avoid:
Avoid extreme heat.Avoid contact withincompatible material.

Materials to Avoid: acid. strong oxidizing agents.

Hazardous Decomposition Products:
oxides of carbon,varioushydrocarbons formed when burned.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

- Inhalation: Mists or sprays of insoluble oils are not harmful to the respiratory tract, although worker discomfort may occur at oil mist level of 5 mg/m³.
- Skin Contact: May cause hair follicles, comedones, perifollicular papules and pustules. Some individuals may develop a skin sensitivity to petroleum products.
- Eye Contact: Found to be moderately irritating to rabbit eyes.
- Ingestion: Mineral oils may cause gastrointestinal disturblance such as diarrhea.

Local Effect: No data available.

Sensitization: No data available.

Chronic Toxicity:

- Inhalation: Repeated or prolonged contact with oils may cause fibrotic nodules, lipoid pneumonia, and lipid granuloma.
- Skin Contact: Repeated or prolonged contact may cause defatting of the skin which may result in dermatitis and effect as detailed in acute exposure.
- Eye Contact: Repeated or prolonged contact with irritants may cause conjunctivitis.
- Ingestion: No data available.

Specific Effects: No data available.

XII. ECOLOGICAL INFORMATION

Environmental Mobility: Fates: This material is not expected to present any environmental problems other than those associated with oil spills.

XIII. DISPOSAL CONSIDERATIONS

Subject to disposal regulations:
Dispose in accordance with all applicable regulations.

XIV. TRANSPORT INFORMATION

Not dangerous for conveyance.

XV. REGULATORY INFORMATION

Suitable Regulations:

1. All components comply with EINECS, TSCA, DSL, AICS, ECL and MITI.
2. EC dangerous substances/preparations classification: not regulated.

XVI. OTHER INFORMATION

Reference Literatures	OHS 11250
Made By	Lubricants Business Division, CPC Corporation, Taiwan
Creation Date	2026-03-01

CPC Corporation, Taiwan (CPC) believes that the information contained herein (including data and statements) is accurate as of the date hereof.

NO ANY WARRANTY, EXPRESS OR IMPLIED, IS MADE ASCONCERNS THE INFORMATION HEREIN PROVIDED.

The information provided herein relates only to the specific product designated and may not be valid not be valid where such product is used in combination with any other materials or in any process. Further, since the conditionsand methods of use of the product and information referred to herein arebeyond the control ofCPC.

CPC expressly disclaims any and all liabilityas to any results obtained or arising from any use of product or such information.